

Safety Data Sheet

IMO (International Maritime Organization) MSDS
per SOLAS regulation VI/5-1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name	:	Kerosene
Supplier	:	Shell Trading Rotterdam B.V. Weena 70 3012 CM Rotterdam Netherlands
Contact Telephone	:	+31 10 441 5000
Emergency Telephone Number	:	+1 703-527-3887
MARPOL Annex I Category	:	Kerosenes
Description on Bill of Lading (B/L)/Bunker delivery note/Shipping document	:	Jet Fuels (Annex 1, Appendix 1 Name)
Other Information	:	See Section 14 for transportation information related to the Bill of Lading, other shipping documents.

2. HAZARDS IDENTIFICATION

GHS Classification	:	FLAMMABLE LIQUIDS, Category 3 Specific target organ toxicity - single exposure, Category 3, narcotic effects ASPIRATION HAZARD, Category 1 SKIN CORROSION/IRRITATION, Category 2 AQUATIC TOXICITY (CHRONIC), Category 2 AQUATIC TOXICITY (ACUTE), Category 2
---------------------------	---	---

GHS Label Elements
Symbol(s)



Signal Words	:	Danger
GHS Hazard Statements	:	PHYSICAL HAZARDS: H226: Flammable liquid and vapor. HEALTH HAZARDS: H304: May be fatal if swallowed and enters airways. H336: May cause drowsiness or dizziness. H315: Causes skin irritation. ENVIRONMENTAL HAZARDS: H411: Toxic to aquatic life with long lasting effects. H401: Toxic to aquatic life.

GHS Precautionary Statements

Prevention	:	P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking. P240: Ground/bond container and receiving equipment.
-------------------	---	---

Safety Data Sheet

IMO (International Maritime Organization) MSDS per SOLAS regulation VI/5-1

P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P271: Use only outdoors or in a well-ventilated area.
P264: Wash hands thoroughly after handling.
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P281: Use personal protective equipment as required.
P273: Avoid release to the environment.

- Response** : P303+P361+P353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331: Do NOT induce vomiting.
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P321: Specific treatment (see details on this label).
P332+P313: If skin irritation occurs: Get medical advice/attention.
P362: Take off contaminated clothing and wash before reuse.
P308+P313: IF exposed or concerned: Get medical advice/attention.
P391: Collect spillage.
P370: In case of fire:
Use appropriate media for extinction.
- Storage** : P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : P501: Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.
- Other Hazards which do not result in classification** : Slightly irritating to respiratory system. Liquid evaporates quickly and can ignite leading to a flash fire, or an explosion in a confined space. Vapour in the headspace of tanks and containers may ignite and explode at temperatures exceeding auto-ignition temperature, where vapour concentrations are within the flammability range. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. May ignite on surfaces at temperatures above auto-ignition

Safety Data Sheet

IMO (International Maritime Organization) MSDS per SOLAS regulation VI/5-1

Additional Information : temperature.
: This product is intended for use in closed systems only.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Preparation Description : Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons with carbon numbers predominantly in the C9 to C16 range. May also contain several additives at <0.1% v/v each. May contain cetane improver (Ethyl Hexyl Nitrate) at <0.2% v/v.

Hazardous Components

Chemical Identity	CAS	Conc.
Kerosine	8008-20-6	100.00 %

Additional Information : Contains Naphthalene, CAS # 91-20-3. Dyes and markers can be used to indicate tax status and prevent fraud.

4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

Skin Contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye Contact : Flush eyes with water while holding eyelids open. Rest eyes for 30 minutes. If redness, burning, blurred vision, or swelling persist, transport to the nearest medical facility for additional treatment.

Ingestion : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (37° C), shortness of breath, chest congestion or continued coughing or wheezing. Give nothing by mouth.

Most Important Symptoms/Effects, Acute & Delayed : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death. Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.

Immediate medical attention, special : Treat symptomatically. Potential for chemical pneumonitis.

Safety Data Sheet

IMO (International Maritime Organization) MSDS
per SOLAS regulation VI/5-1

treatment

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

- Specific hazards arising from Chemicals** : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Oxides of sulphur. Unidentified organic and inorganic compounds. Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. Flammable vapours may be present even at temperatures below the flash point.
- Suitable Extinguishing Media** : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable Extinguishing Media** : Do not use water in a jet.
- Protective Equipment & Precautions for Fire Fighters** : Wear full protective clothing and self-contained breathing apparatus.
- Additional Advice** : Keep adjacent containers cool by spraying with water.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations. Evacuate the area of all non-essential personnel. Ventilate contaminated area thoroughly.

- Personal Precautions, Protective Equipment and Emergency Procedures** : Do not breathe fumes, vapour. Do not operate electrical equipment.
- Environmental Precautions** : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment (of product and fire fighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Methods and Material for Containment and Clean Up** : For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as

Safety Data Sheet

IMO (International Maritime Organization) MSDS per SOLAS regulation VI/5-1

contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Shovel into a suitable clearly marked container for disposal or reclamation in accordance with local regulations.

- Additional Advice** :
- Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.

7. HANDLING AND STORAGE

- General Precautions** :
- Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Prevent spillages. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Never siphon by mouth. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. Maintenance and Fuelling Activities - Avoid inhalation of vapours and contact with skin.
- Precautions for Safe Handling** :
- Avoid inhaling vapour and/or mists. Avoid prolonged or repeated contact with skin. When using do not eat or drink. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Earth all equipment. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. The vapour is heavier than air, spreads along the ground and distant ignition is possible.
- Conditions for Safe Storage** :
- Drum and small container storage: Drums should be stacked to a maximum of 3 high. Use properly labelled and closeable containers. Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Vapours from tanks should not be released to atmosphere. Breathing losses during storage should be controlled by a suitable vapour treatment system. The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Keep in a bunded area with a sealed (low permeability) floor, to provide containment against spillage. Prevent ingress of water. Use properly labelled and closeable containers.
- Product Transfer** :
- Avoid splash filling. Wait 2 minutes after tank filling (for tanks

Safety Data Sheet

**IMO (International Maritime Organization) MSDS
per SOLAS regulation VI/5-1**

such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Keep containers closed when not in use. Do not use compressed air for filling, discharging or handling. Contamination resulting from product transfer may give rise to light hydrocarbon vapour in the headspace of tanks that have previously contained gasoline. This vapour may explode if there is a source of ignition. Partly filled containers present a greater hazard than those that are full, therefore handling, transfer and sampling activities need special care.

- Container Advice** : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.
- Other Advice** : Ensure that all local regulations regarding handling and storage facilities are followed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Type	ppm	mg/m3	Notation
Kerosine	ACGIH	TWA [Non-aerosol.]		200 mg/m3	P: Application restricted to conditions in which there are negligible aerosol exposures. as total hydrocarbon vapor
	ACGIH	SKIN_DES [Non-aerosol.]			Can be absorbed through the skin. as total hydrocarbon vapor
Naphthalene	ACGIH	TWA	10 ppm		
	ACGIH	STEL	15 ppm		
	ACGIH	SKIN_DES			Can be absorbed through the skin.

- Additional Information** : Skin notation means that significant exposure can also occur by absorption of liquid through the skin and of vapour through the eyes or mucous membranes.

Biological Exposure Index (BEI) - See reference for full details
No biological limit allocated.

Safety Data Sheet

IMO (International Maritime Organization) MSDS per SOLAS regulation VI/5-1

- Appropriate Engineering Controls** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.
Appropriate measures include: Use sealed systems as far as possible. Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Local exhaust ventilation is recommended. Eye washes and showers for emergency use.
- Individual Protection Measures** : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Respiratory Protection** : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. All respiratory protection equipment and use must be in accordance with local regulations.
- Hand Protection** : Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Select gloves tested to a relevant standard (e.g. Europe EN374, US F739). When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.
- Eye Protection** : Chemical splash goggles (chemical monogoggles).
- Protective Clothing** : Chemical resistant gloves/gauntlets, boots, and apron (where risk of splashing).
- Thermal Hazards** : Not applicable.
- Monitoring Methods** : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
- Environmental Exposure Controls** : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : Clear colourless. Liquid.
Odour : Hydrocarbon
Odour threshold : Data not available

Safety Data Sheet

IMO (International Maritime Organization) MSDS per SOLAS regulation VI/5-1

pH	: Data not available
Initial Boiling Point and Boiling Range	: > 160 °C / 320 °F
Melting / freezing point	: <= 12.44 °C / 54.39 °F
Flash point Lower / upper	: > 37.8 °C / 100.0 °F (Tag Closed Cup (ASTM D56))
Flammability or Explosion limits	: 0.7 - 5.0 %(V)
Auto-ignition temperature	: 229 °C / 444 °F
Vapour pressure	: 0.013 hPa at 38 °C / 100 °F
Relative Density	: 0.8 - 0.82
Water solubility	: Negligible.
Solubility in other solvents	: Data not available
n-octanol/water partition coefficient (log Pow)	: Data not available
Dynamic viscosity	: Data not available
Kinematic viscosity	: Data not available
Vapour density (air=1)	: 4.5
Evaporation rate (nBuAc=1)	: Data not available
Flammability	: Flammable liquid.

10. STABILITY AND REACTIVITY

Chemical Stability	: Stable under normal conditions of use.
Possibility of Hazardous Reactions	: Data not available
Conditions to Avoid	: Avoid heat, sparks, open flames and other ignition sources.
Incompatible Materials	: Strong oxidising agents.
Hazardous Decomposition Products	: Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

11. TOXICOLOGICAL INFORMATION

Basis for Assessment	: Information given is based on product data, a knowledge of the components and the toxicology of similar products.
Likely Routes of Exposure	: Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.
Acute Oral Toxicity	: Low toxicity: LD50 > 5000 mg/kg , Rat
Acute Dermal Toxicity	: Low toxicity: LD50 >2000 mg/kg , Rabbit
Acute Inhalation Toxicity	: Low toxicity by inhalation. LC50 >5 mg/l , 4 h, Rat
Skin Corrosion/Irritation	: Irritating to skin.

Safety Data Sheet

IMO (International Maritime Organization) MSDS per SOLAS regulation VI/5-1

Serious Eye Damage/Irritation	:	Expected to be slightly irritating.
Respiratory Irritation	:	Inhalation of vapours or mists may cause irritation to the respiratory system.
Respiratory or Skin Sensitisation	:	Not a skin sensitiser.
Aspiration Hazard	:	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
Germ Cell Mutagenicity	:	Not considered a mutagenic hazard.
Carcinogenicity	:	Not classified as a carcinogen. Repeated skin contact has resulted in irritation and skin cancer in animals. (Naphthalene)
Reproductive and Developmental Toxicity	:	Not expected to be a developmental toxicant. Not expected to impair fertility.
Specific target organ toxicity - single exposure	:	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.
Specific target organ toxicity - repeated exposure	:	Kidney: caused kidney effects in male rats which are not considered relevant to humans

12. ECOLOGICAL INFORMATION

Basis for Assessment	:	Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Acute Toxicity	:	Toxic: LL/EL/IL50 1-10 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Fish	:	Toxic: LL/EL/IL50 1-10 mg/l
Aquatic Invertebrates	:	Toxic: LL/EL/IL50 1-10 mg/l
Algae	:	Toxic: LL/EL/IL50 1-10 mg/l
Microorganisms	:	Practically non toxic: LL/EL/IL50 > 100 mg/l
Mobility	:	Floats on water. Contains volatile constituents. Evaporates within a day from water or soil surfaces. Large volumes may penetrate soil and could contaminate groundwater.
Persistence/degradability	:	Not Persistent per IMO criteria. International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof." Expected to be inherently biodegradable. The volatile constituents will oxidize rapidly by photochemical reactions in air.
Bioaccumulative	:	Contains constituents with the potential to bioaccumulate.

Safety Data Sheet

IMO (International Maritime Organization) MSDS
per SOLAS regulation VI/5-1

**Potential
Other Adverse Effects** : Films formed on water may affect oxygen transfer and damage organisms.

13. DISPOSAL CONSIDERATIONS

Material Disposal : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Container Disposal : Send to drum recoverer or metal reclaimer. Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard if heated above the flash point. Do not puncture, cut or weld uncleaned drums. Do not pollute the soil, water or environment with the waste container. Comply with any local recovery or waste disposal regulations.

Local Legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Regulated

Class : 3
Packing group : III
Hazard identification no. : 30
UN No. : 1223
Danger label (primary risk) : 3
Proper shipping name : KEROSENE

IMDG

Identification number : UN 1223
Proper shipping name : KEROSENE
Class / Division : 3
Packing group : III
Environmental Hazard: Yes

Safety Data Sheet

IMO (International Maritime Organization) MSDS per SOLAS regulation VI/5-1

IATA (Country variations may apply)

UN No. : 1223
Proper shipping name : Kerosene
Class / Division : 3
Packing group : III

Additional Information : This product is being carried under the scope of MARPOL Annex I.
Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Classification triggering components : Contains kerosine.

16. OTHER INFORMATION

Additional Information : This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters.

MSDS Version Number : 1.0

MSDS Effective Date : 10.12.2010

MSDS Revisions : A vertical bar (|) in the left margin indicates an amendment from the previous version.

MSDS Distribution : The information in this document should be made available to all who may handle the product.

Disclaimer : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.